

Redexim



RENOVATION
for Natural and Synthetic Turf



Synthetic Turf



Verti-Rake

The Verti-Rake decompacts turf surfaces using tines to scratch through infill while lifting turf fibers to stand like new, allowing oxygen and nutrients into the turf resulting in a healthier playing field. The thin, flexible, spring-loaded tines are integrated in a special protection device that will prevent their loss during operation.

The Verti-Rake is ideal to use on those occasions when the turf fibers have become covered by infill due to a variety of causes.

FEATURE	BENEFIT
Flexible Tines	Decompacts infill while lifting turf fibers
Optional Brush	Versatile piece
Light Weight	Can be used with most compact tractors



Verti-Rake



SPECIFICATIONS		DESCRIPTION			
MODEL	1500	2000	3000	4500	6000
Working Width	59" (1.5 m)	81.9" (2.08 m)	118.1" (3.0 m)	177.2" (4.5 m)	236" (6.0 m)
Working Depth	Surface processing	Surface processing	Surface processing	Surface processing	Surface processing
Maximum Speed	7.5 mph (12 kph)	7.5 mph (12 kph)	7.5 mph (12 kph)	7.5 mph (12 kph)	7.5 mph (12 kph)
Weight	453 lbs (206 kg)	497 lbs (226 kg)	606 lbs (275 kg)	1,213 lbs (550 kg)	1,488 lbs (675 kg)
Recommended Tractor	18 hp with minimum lifting capacity of 661.4 lbs (300 kg)	18 hp with minimum lifting capacity of 661.4 lbs (300 kg)	18 hp with minimum lifting capacity of 881.9 lbs (400 kg)	- 30 hp with minimum lifting capacity of 1,433 lbs (650 kg) - 1 single acting valve	30 hp with minimum lifting capacity of 1,763.7 lbs (800 kg)
Maximum Capacity (Theoretical at Maximum Speed of 7.5 mph [12 kph])	193,750 sq. ft./h (18,000 sq. m./h)	268,667 sq. ft./h (24,960 sq. m./h)	387,500 sq. ft./h (36,000 sq.m./h)	581,251 sq. ft./h (54,000 sq. m./h)	775,001 sq. ft./h (72,000 sq. m./h)
Distance Between Pins	0.6" (15 mm)	0.6" (15 mm)	0.6" (15 mm)	0.6" (15 mm)	0.6" (15 mm)
Shipping Dimensions (L x W x H)	63" x 37.8" x 80.7" (1,600 mm x 960 mm x 2,050 mm)	82.7" x 37.8" x 80.7" (2,100 mm x 960 mm x 2,050 mm)	63" x 63" x 80.7" (1,600 mm x 1,600 mm x 2,050 mm)	71.3" x 102.5" x 72.8" (1,810 mm x 2,800 mm x 1,850 mm)	71.7" x 118" x 102.4" (1,810 mm x 2,995 mm x 2,600 mm)
Three-Point Connection	Cat. 1 - 2	Cat. 1 - 2	Cat. 1 - 2	Cat. 1 - 2	Cat. 1 - 2
Grease	EP 2	EP 2	EP 2	EP 2	EP 2
Standard Components	- Running wheels adjustable in height - Verti-Rake pin section - Toolbox including a manual	- Running wheels adjustable in height - Verti-Rake pin section - Toolbox including a manual	- Running wheels adjustable in height - Verti-Rake pin section - Toolbox including a manual	- Running wheels adjustable in height - Verti-Rake pin section - Toolbox including a manual	- Running wheels adjustable in height - Verti-Rake pin section - Toolbox including a manual
Optional	Brush set	Brush set	Brush set	Brush set	Brush set

